

Fixed - White Powder Coated Galvalume™

These bright white polyester finished Galvalume™ ladders will make a durable and attractive addition to your dock, seawall or any marine application. Heavy 1½" (3.8cm) tubing ensures a positive grip. Extra wide 3.75" (95mm) steps for a sure footing. Easy to assemble & includes stainless steel hardware. 400lb (180kg). Capacity.

Value Level: Entry
Rail Height: 18½" (47cm)
Tread Depth: 3¾" (9.5cm)
Tread Width: 14" (35.6cm)
Distance to first step: 12" (30.5cm)
Distance between treads: 11" (27.9cm)




PART #	DESCRIPTION
DE2103F	3-Step, Complete
DE2104F	4-Step, Complete
DE2105F	5-Step, Complete

Kwik Release

This ladder is manufactured with 1" heavy wall aluminum tubing. All assembly hardware is stainless steel and assembly is quick and easy. Simply tilt the ladder up and slide it out for storage and cleaning, or mount the ladder permanently with its' pre-drilled holes. 450lb (204kg) Capacity.

Value Level: Better
Rail Height: 19" (48.3cm) above the dock.
Tread Depth: 5¼" (13.3cm)
Tread Width: 16.1" (40.9cm)
Distance to first step: 9½" (23.2cm)
Distance between treads: 11" (27.9cm)



PART #	DESCRIPTION
DE2003F	3-Step, Complete
DE2004F	4-Step, Complete
DE2005F	5-Step, Complete

Fixed - ECO² Weld-Free, Marine Grade Aluminum

These durable ladders have been designed to make a minimum carbon footprint. It is manufactured with no welding processes involved. Easily assembles in a few minutes with Stainless Steel fasteners. Wider steps make it better for a sure grip and safe climb. Easily accommodate weights up to 500lb (227kg).

Value Level: Good
Rail Height: 18" (45.7cm)
Tread Depth: 2½" (6.4cm)
Tread Width: 14" (35.6cm)
Distance to first step: 10" (25.4cm)
Distance between treads: 11" (27.9cm)



PART #	DESCRIPTION
DE2073F	3-Step, Complete
DE2074F	4-Step, Complete
DE2075F	5-Step, Complete



Stand-Off - Welded, Marine Grade Aluminum with Quick Release

These Stand-off ladders are easy to assemble and made from Heavy-wall 1" marine grade aluminum extrusion with large aluminum steps for a sure footing. Stainless Steel assembly hardware is included. A great light weight, durable addition for any application and ideal for pontoon boats. 350lb (159kg) Capacity.

Value Level: Better
Rail Height: 18" (45.7cm)
Tread Depth: 5¼" (13.3cm)
Tread Width: 16.1" (40.9cm)
Distance to first step: 9½" (23.2cm)
Distance between treads: 11" (27.9cm)

PART #	DESCRIPTION
DE2153F	3-Step, Complete
DE2154F	4-Step, Complete
DE2155F	5-Step, Complete
DE2157F	7-Step, Complete



Flip-Up - ECO² Weld-Free, Marine Grade Aluminum

Designed to make a minimum carbon footprint, these ladders are manufactured with no welding processes involved to reduce material waste and save energy. Easy to assemble & includes stainless steel hardware. Ribbed anti-slip steps for a sure footing. 500lb (227kg) Capacity.

Value Level: Good
Rail Height: 18½" (47.0cm)
Tread Depth: 2½" (6.4cm)
Tread Width: 14" (35.6cm)
Distance to first step: 10½" (26.7cm)
Distance between treads: 11" (27.9cm)




PART #	DESCRIPTION
DE2173F	3-Step, Weld Free, Flip-Up, Complete
DE2174F	4-Step, Weld Free, Flip-Up, Complete
DE2175F	5-Step, Weld Free, Flip-Up, Complete



Fixed - Wide Step. Welded, Marine Grade Aluminum

These durable ladders are ideal for sure-footed access to and from the water or boat and with a load capacity of 665lb (300kg) these rugged ladders will stand the test of time. 4" (10 cm) x 16.75" (42.5 cm) ribbed anti-slip steps. Clean, smooth, mill finish aluminum and welded construction. Large diameter gables and rails for strength and a sure grip. Easy to assemble & includes stainless steel hardware. Perfect for seawalls or dock applications with varying water levels.

Value Level: Best
Rail Height: 19½" (49.5cm)
Tread Depth: 4" (10.2cm)
Tread Width: 16¾" (42.5cm)
Distance to first step: 11" (27.9cm)
Distance between treads: 12" (30.5cm)



PART #	DESCRIPTION
DE2043F	3-Step, Complete
DE2044F	4-Step, Complete
DE2045F	5-Step, Complete
DE2047F	7-Step, Complete

Flip-Up - Wide Step. Welded, Marine Grade Aluminum

With 4" (10 cm) x 16.75" (42.5 cm) ribbed anti-slip steps, these ladders flip up and out of the water when not in use, and are easily secured in the up or down position with a handy retainer pin. Clean, smooth, mill finish aluminum and welded construction. Large diameter gables and rails for strength and a sure grip. Easy to assemble & includes stainless steel hardware. 665lb (300kg) Capacity.

- Value Level: Best
- Rail Height: 19½" (49.5cm)
- Tread Depth: 4" (10.2cm)
- Tread Width: 16¼" (42.5cm)
- Distance to first step: 11" (27.9cm)
- Distance between treads: 12" (30.5cm)

PART #	DESCRIPTION
DE2123F	3-Step, Complete
DE2124F	4-Step, Complete
DE2125F	5-Step, Complete
DE2127F	7-Step, Complete



Swing-Up - Rotomolded

Tough and durable, this rotomolded ladder swings up and out of the way, locking in place when not in use. Will not corrode with exposure and will not fade or crack. Molded-in U.V. inhibitors and fungicides. 500lb (227kg) Capacity. 4 Steps, Polyethylene, Stainless Steel assembly hardware.

- Value Level: Premium
- Gable Height: 20½" (52.1cm)
- Tread Depth: 4" (10.2cm)
- Tread Width: 14" (35.6cm)
- Distance to first step: 11¾" (29.8cm)
- Distance between treads: 10½" (26.7cm)

GREY	SAND	DESCRIPTION
DE2064F	DE2164F	4-Step, Swing Up



Stand Off - Rotomolded

With the same great features of the Swing-Up, the Stand Off rotomolded ladder extends into the water at a 60° angle to make getting out of the water easier. 500lb (227kg) Capacity.

- Value Level: Premium
- Gable Height: 20½" (52.1cm)
- Tread Depth: 6½" (16.5cm)
- Tread Width: 14" (35.6cm)
- Distance to first step: 12½" (31.8cm)
- Distance between treads: 10½" (26.7cm)



GREY	SAND	DESCRIPTION
DE2084F	DE2184F	4-Step, Swing Up, Stand Off



MATERIAL	VALUE LEVEL	CONSTRUCTION	KEY FEATURE	FRAME	STEP WIDTH	STEP DEPTH	SERIES	IMAGE	STYLE	RATING (lbs)	STEPS
Galvalume (Steel)	Entry	Bolted	Powder Coated	1½" Round	14"	3¾"	210x		Fixed Straight	400	3,4,5
Aluminum	Good	Bolted	ECO	1½" Round	14"	2½"	207x		Fixed Straight	500	3,4,5
					14"	2½"	217x		Flip-Up Straight	500	3,4,5
	Better	Welded	Quick Release	1" Square	16.1"	5¼"	200x		Fixed Straight	450	3,4,5
					16.1"	5¼"	215x		Fixed Stand-Off	350/300	3,4,5,7
	Best	Welded	Premium	1⅞" Round	16¾"	4"	204x		Fixed Straight	665	3,4,5,7
					16¾"	4"	212x		Flip-Up Straight	665	3,4,5,7
LDPE	Premium	Roto-Molded	Grey & Sand	Roto	14"	4"	2x64		Flip-Up Straight	500	4
					14"	6½"	2x84		Flip-Up Stand-Off	500	4