SIONYX 504 O NIGHTVAVE D1

ULTRA LOW-LIGHT MARINE CAMERA

MODEL CRV-500C SKU C012800 UPC-A 811251020149

Nightwave is an ultra low-light camera built around SIONYX's patented Black Silicon CMOS sensor. Nightwave gives professional mariners the ability to easily spot hazards and debris in moonless starlight without white light or expensive thermal cameras – navigating safely, avoiding collisions, and maximizing time on the water. IP67 rated, it's built to operate in the toughest marine environments.

Nightwave offers maritime professional agencies such as the Coast Guard, Harbor Patrol, and Border Patrol color digital night vision for surveillance and evidencegathering, search & rescue, and covert operations. With the most advanced digital color night vision in the world, SIONYX Nightwave will guide you safely through any maritime environment.

| CONNECTED | Seamless integration with major brand MFDs via the analog video output. Convenient installation flexibility with built in WiFi video streaming and communication. |
|-----------|--|
| RUGGED | IP67 rated, submersible to 3 ft for 30 minutes. You can safely use Nightwave in inclement weather conditions. |
| CAPABLE | <1 MLX MOONLESS STARLIGHT sensitivity allows you to see well beyond human eyesight & detect a man-sized object at 150 meters. |
| AWARE | 40° field of view increases situational awareness to spot unexpected obstacles, debris, markers, vessels, and more. |

SIONYX

CAMERA

| SENSOR TYPE | XQE1350 BSI CMOS |
|------------------|------------------|
| RESOLUTION | 1280 X 1024 |
| FRAME RATE | 60 HZ |
| HORIZONTAL FOV | 40° |
| VISIBLE SPECTRUM | 400-1100NM |
| FOCUS RANGE | 10M TO INFINITY |
| LENS | 16MM F/1.4 |

SYSTEM

| VIDEO OUT | NTSC/PAL |
|-------------------------|--------------------|
| VIDEO CONNECTION | BNC |
| WIRELESS COMMUNICATIONS | WIFI + BLUETOOTH |
| POWER IN | 12V DC |
| POWER CONNECTION | TINNED COPPER WIRE |

PHYSICAL

| WEIGHT | 870 G [1.9 LBS] |
|------------------|------------------------------------|
| DIMENSIONS | 127 X 127 X 152 MM [5 X 5 X 6 IN] |
| MOUNTING OPTIONS | TRIPOD OR RAMMOUNT |
| | SINGLE 1/4" 20 CENTER MOUNT |
| | BULKHEAD MOUNT: 4 X M6 BLIND HOLES |
| | TOP-DOWN MOUNTING HOLES |
| MATERIAL | UV RESISTANT POLYCARBONATE |
| | |

INCLUDED

| CAMERA | BASE GASKET |
|--------------------------|-------------------|
| CABLE [5M] | MOUNTING HARDWARE |
| BNC TO RCS CONVERTER | INSTALL TEMPLATE |
| POWER FUSE & FUSE HOLDER | USER MANUAL |
| DIGITAL VIDEO CABLE USB | |

ENVIRONMENTAL

| INGRESS PROTECTION | IP67 WATER/DUST RESISTANT |
|-----------------------|-------------------------------|
| SHOCK & VIBRATION | IEC60945 [V15G H:9G] IK08 |
| OPERATING TEMPERATURE | -20°C TO +50°C |
| STORAGE TEMPERATURE | -20°C TO +80°C |

RANGE PERFORMANCE

| CLEAR WEATHER AT 1/4 MOON |
|---------------------------|
| 150 M |


| DETECT MAN-SIZED OBJECT | |
|-------------------------|--|
| | |

All product, product specification, and data are subject to change without notice to improve reliability, function, design, or otherwise. Visit SIONYX.COM for up-to-date documentation.

EYESIGHT VS NIGHTWAVE



127 MM | 5 IN



DEPTH: 127 MM | 5 IN



SIONYX.COM | info@sionyx.com | (978) 922-0684 100 Cummings Center | Suite 303B | Beverly, MA 01915 | USA Get connected with the SIONYX Nightwave Mobile App



Google Play